

STT	Mã VT	Tên vật tư	Tên vật tư sau chuẩn hóa	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Mã đặt hàng/ Mã Vật tư/ Bản vẽ	Số lượng	Ghi chú
1	33441095	Bộ biến tần Convertteam - Type: ALSPA MD2000 -144-400	Frequency Converter	BO	INVERTER; ELECTRICAL POWER RATING: 110 kW TYPE: ALSPA MD2000 ,115/144-400 SIZE: Frame 2E INPUT VOLTAGE: 400 V OUTPUT VOLTAGE: 400 V CURRENT RATING: 208 A FREQUENCY: 0 to 300 Hz APPLICATION: MBU32AP001 Nox Water Pump	ALSPA MD2000 ,115/144-400	1,00	
2	89130300	Dàn giải nhiệt máy lạnh. Heating FN 43 Meluck 6HP Kích thước: 1015x180x680mm. Heating cap:14.8kW	Air cooled condenser	BO	COOLING SYSTEM TYPE: FN-43 SIZE: 1015 * 180 * 680 mm MANUFACTURER: Meluck CAPACITY: 14.8 kW ADDITIONAL INFORMATION: Use for air condition: 6 HP		1,00	
3	58730001	Màn hình HMI (Operator Panel)	OP3 Operator Panel	CAI	DISPLAY SCREEN; OTHER TYPE: 1p6AV3503- 1DB10 SIZE: W 148 * H 76 mm POWER SUPPLY RATING: 24VDC/ 160mA ADDITIONAL INFORMATION: MANUFACTURER: Siemens; SVPV2308897	1p6AV3503- 1DB10	1,00	
4	58730001	Màn hình HMI (Operator Panel)	OP3 Operator Panel	CAI	DISPLAY SCREEN; OTHER TYPE: 1p6AV3503- 1DB10 SIZE: W 148 * H 76 mm POWER SUPPLY RATING: 24VDC/ 160mA ADDITIONAL INFORMATION: MANUFACTURER: Siemens; SVPV2308897	1p6AV3503- 1DB10	1,00	

5	56297915	Đầu dò nhiệt WMX 1000D105Ex . Operating Temperature Range:-20 °C to +80 °C (-4 °F to +176 °F). 9VDC. MINIMAX; Material:White polycarbonate; Order No:907368;	Heat Detector	CAI	DETECTOR; HEAT TYPE: WMX 1000D105 Ex POWER SUPPLY: 9 VDC OPERATION AMBIENT: -20 to 80 deg C (-4 to 176 deg F) MATERIAL: White polycarbonate MANUFACTURER: Minimax ADDITIONAL INFORMATION: Order No: 907368; S/n: 100430908-1	WMX 1000D105 Ex	1,00	
6	56333372	Van điều áp B72G - 2GK - SD1 - RMG. Dây làm việc 0,3...10bar	Filter regulato	CAI	REGULATOR; PRESSUREMODEL: B72GTYPE: B72G - 2GK - SD1 - RMGWIDTH: 48.5 mmPRESSURE RATING: 0.3 to 10 barOUTLET SIZE: 1/4 inMATERIAL: Body: ZincLENGTH: 50.5 mmINLET SIZE: 1/4 inHEIGHT: 207 mmFLOW RATE: 38 dm3/sTEMPERATURE RATING: Tranparent bowl: -34 to 50 deg C; Metal bowl: -34 to 65 deg C ADDITIONAL INFORMATION: MANUFACTURER: Norgren	B72G/B72G - 2GK - SD1 - RMG	1,00	
7	56072135	SPRING RETURN MOTOR AF24- SC7/PART.NO.10320	Spring return motor AF24-SC7	PC	MOTOR; OTHER VOLTAGE RATING: 24 V AC/DC; 50/60 Hz ADDITIONAL INFORMATION: PART.NO.: 10320; Model: AF24 – S – C7; Open/ Close: 2 x SPDT; MANUFACTURER: BELIMO	AF24 – S – C7/ 10320	1,00	
8	56065005	PROCESSOR MODULE PM665 Art No 3BDS005799R1 (cài sẵn Base Software)	Processor Module	CAI	CONTROLLER; DEVICES TYPE: PM665 DIMENSION: L 252 * H 273 * W 40 mm MANUFACTUER: ABB APPLICATION: Base Software installed ADDITIONAL INFORMATION: Art No: 3BDS005799R1; PR: N	PM665	1,00	
9	56065005	PROCESSOR MODULE PM665 Art No 3BDS005799R1 (cài sẵn Base Software)	Processor Module	CAI	CONTROLLER; DEVICES TYPE: PM665 DIMENSION: L 252 * H 273 * W 40 mm MANUFACTUER: ABB APPLICATION: Base Software installed ADDITIONAL INFORMATION: Art No: 3BDS005799R1; PR: N	PM665	1,00	

10	51990499	Air dryer's Valve CD3+	Air dryer's Valve CD3+	CAI	VALVE; OTHER MODEL/PART NUMBER: Air dryer model: 8102-3200-44 TYPE: Air dryer Type: CD3+ MANUFACTURER: Atlas Copco/ UK ADDITIONAL INFORMATION: Ref. No.: 5020; See attachment "CD 3+ APIW - 30709401 Part list" page 22,23 for detail		1,00	
11	39507001	Air dryer's Controller CD3+	Air dryer's Controller CD3+	BO	CONTROLLER; PNEUMATICMODEL: Air dryer model: 8102-3200-44TYPE: Air dryer Type: CD3+MANUFACTUER: Atlas Copco/ UKADDITIONAL INFORMATION: Ref. No.: 5030; See attachment "CD 3+ APIW - 30709401 Part list" page 22,23 for detail		1,00	
12	88529006	PanelView Plus 700	PanelView Plus 700	CAI	SCREEN; MONITOR PART NUMBER: Catalog Number: 2711P- RDB7C SIZE: 700 keypad, or keypad and touch: H 193 * W 290 * D 55; 700 touch: H 179 * W 246 D 55 mm ADDITIONAL INFORMATION: Input voltage: 24 VDC; MANUFACTURER: Allen- Bradley	2711P-RDB7C	1,00	
13	41861004	Conventional Fire Alarm Control Panel; 4 zone conventional FACP Red 230V; W 385 * H 310 * D 92 mm	Conventional Fire Alarm Control Pane	CAI	PANEL; CONTROL TYPE: 4 zone conventional FACP Red 230V SIZE: W 385 * H 310 * D 92 mm MATERIAL: 1.2mm mild steel POWER RATING: Supply Voltage: 120VAC (50hz/60hz) or 220VAC (50hz/60hz); Power Supply DC Rating: 24V/ 3Amps ADDITIONAL INFORMATION: Model: HCV-4/230V; Max. Battery Size: 7Ah/ 12V (2 per panel); MANUFACTURER: Hochiki America Corporation	SS-10M0-1-8	1,00	

14	56073210	"NEEDLE VALVE EM-V202 IN: 1/4 NPT-F OUT: 1/4 NPT-F. KWZ7016124P0066.	Needle valve	PC	VALVE; NEEDLE TYPE: 1000CBABABAA BONNET TYPE: Std bonnet PACKING MATERIAL: PTFE PRESSURE RATING: 6000 psi BODY MATERIAL: SS 316L NOMINAL PIPE SIZE: 1/4 in NPT-F ADDITIONAL INFORMATION: KWZ7016124P0066	1000CBABABAA	1,00	
15	56073210	"NEEDLE VALVE EM-V202 IN: 1/4 NPT-F OUT: 1/4 NPT-F. KWZ7016124P0066.	Needle valve	PC	VALVE; NEEDLE TYPE: 1000CBABABAA BONNET TYPE: Std bonnet PACKING MATERIAL: PTFE PRESSURE RATING: 6000 psi BODY MATERIAL: SS 316L NOMINAL PIPE SIZE: 1/4 in NPT-F ADDITIONAL INFORMATION: KWZ7016124P0066	1000CBABABAA	1,00	
16	48272320	Cút nối đồng thau máy nén sân trạm 1 đầu ren ngoài ĐK: 32x22mm	Brass connector	CAI	CONNECTOR; COPPERTYPE: Male ThreadSIZE: 32x22 mmMATERIAL: BrassEND CONNECTION: Fitting Straight Pipe ConnectorAPPLICATION: Station 220kv compressor		1,00	
17	48272440	Cút nối đồng thau máy nén sân trạm 1 đầu ren ngoài ĐK: 44x35mm	Brass connector	CAI	CONNECTOR; COPPER TYPE: Male Thread SIZE: D44*d35 mm MATERIAL: Brass END CONNECTION: Fitting Straight Pipe Connector APPLICATION: Station 220kv compressor		1,00	

18	89130325	Máy lạnh Reetech 2HP. Model: RC18DD. Công suất 18.800BTU	Air-conditioner Reetech	BO	COOLING SYSTEM TYPE: Outdoor RC-24-BF-A ; indoor RT-24-BF-A MANUFACTURER: Retech CURRENT,FULL LOAD: 11.7 A FREQUENCY: 50 Hz METHOD OF COOLING: R410A CAPACITY: 24000 BTU APPLICATION: Phòng đào tạo KSTT	Model: RC18DD	1,00	
19	50134204	Bearing/Vòng bi 6204 ZZ	Bearing; 6204ZZ	CAI	BEARING; SINGLE ROW BALL(62XX) MODEL/IBI NUMBER/PART NUMBER: 6204ZZ OUTSIDE DIAMETER: 47 mm INSIDE DIAMETER: 20 mm WIDTH: 14 mm MATERIAL: Steel APPLICATION: Motor pump (12MBX22AP001)	6204ZZ	2,00	
20	50124212	Vòng bi 6202-2Z/C3	Ball bearing; 6202-2Z/C3	CAI	BEARING; SINGLE ROW BALL(62XX) MODEL/IBI NUMBER/PART NUMBER: 6202-2Z/C3 OUTSIDE DIAMETER: 35 mm INSIDE DIAMETER: 15 mm WIDTH: 11 mm SEALS/SHIELDS: Shield on both sides	6202-2Z/C3	2,00	
21	48270012	Chèn cơ khí đk trục 12mm của bơm trục ngang Pentax type: INOX100/62	Mechanical insert ring	CAI	SEAL; MECHANICAL SIZE: Shaft diameter: 18, Outer diameter: 31 TEMPERATURE RATING: 20 to 280 deg C MATERIAL SPECIFICATION: SIC/SIC/VITON/SUS304.		2,00	
22	51886406	Quạt làm mát FCU Model: MOD.D1/10-A20010 50/60Hz. 1PH. 4P. 220V. 0.6/0.65A; RPM1300/1450/4SP; CAP 2MFD/450V 54/69W.(Bao gồm cánh quạt)	Cooling fan FCU	BO	MOTOR; SINGLE-PHASE AC (NN):TYPE: YORK MOD.D1/10-A20010PHASE: 1 phaRPM: 1300/1450 rpmPOWER RATING: 54/69 WVOLTS: 220AMPS: 0.6/0.65 AHERTZ: 50 Hz	YORK MOD.D1/10-A20010	2,00	

23	36641462	Bóng đèn chiếu sáng cabin :Bóng đèn led, 60cm, 20w/220V	Philip LED light bulb	BONG	LAMP; LED TYPE: Led WATTS: 20 W VOLTAGE RATING: 220 V SIZE: 60cm	Philip LED light bulb	60,00	
24	36697033	Led lamp (Panel); PL-48SS-6060; 48 W; 220 V	Led lamp (Panel)	CAI	LAMP; LED TYPE: PL-48SS-6060 WATTS: 48 W VOLTAGE RATING: 220 V SIZE: L600*W600*D30 mm SPECIAL REQUIREMENT: 4320 Lm, 6500K	PL-48SS-6060	10,00	
25	89130522	Máy lạnh Daikin 2HP. Model: FTC50NV1V. 18000BTU. Gas: R32 (hoặc R22).	Air conditioner	BO	AIR CONDITION; OTHER TYPE: 2 HP BTU RATING: 18000 BTU MODEL/PART NUMBER: FTC50NV1V or FTF50XV1V PHASE: 1 pha RATED VOLTAGE: 220 to 240 VAC REFRIGERATOR LIQUID: R32 FREQUENCY: 50 Hz MANUFACTURER: Daikin	FTC50NV1V	1,00	
26	25571006	Ống đồng mềm dạng cuộn đk 6mm, dày 0.6mm. 15m/cuộn	Copper pipe	CUON	TUBE; COPPER SIZE: Ø6 mm LENGTH: 15000 mm MATERIAL: COPPER ADDITIONAL INFORMATION: THICKNESS 0.6mm		1,00	
27	25574108	Ống đồng đơ đk 12.7mm, dày 0.7mm (dạng cuộn)	Copper pipe	M	TUBE; COPPER SIZE: Ø12.7 mm MATERIAL: Copper ADDITIONAL INFORMATION: Thickness 0.7 mm		15,00	
28	31544921	Dây điện đôi mềm (2x2.5 mm ²), có vỏ bọc ngoài, 250V, Cadivi	Electric cable 2x2.5 mm ²	M	WIRE; SOFT COPPER 2 CORE TYPE: Vcmd 2x2.5 VOLTAGE RATING: 250 V NUMBER CORE: 2 PACKAGING UNIT: Roi INSULATION MATERIAL: PVC LENGTH: 100m/roi CONDUCTOR MATERIAL: Copper wire	Vcmd 2x2.5	40,00	

29	49082530	Cuộn simili cách nhiệt quấn máy lạnh. Rộng: 80mm. Dài 10000mm	Simili insulation roll for air conditioner wrapping	CUON	MATERIALS; INSULATING ELECTRICAL AND THERMAL OTHER MATERIAL: Simili LENGTH: 10000 mm WIDTH: 80 mm		7,00	
30	487171069	Bảo ôn cách nhiệt ống dẫn gas đơn đk 6mm. dày 9mm	Gas pipe insulation therma	M	MATERIALS; INSULATING ELECTRICAL AND THERMAL OTHER SIZE: Φ6 mm MATERIAL: Foam THICKNESS: 9 mm		20,00	
31	48717028	Bảo ôn cách nhiệt ống dẫn gas đk 12.7mm	Pipe Insulation Foam	M	MATERIALS; HEAT RESISTANT OTHER SIZE: Φ 12.7 mm TEMPERATURE RATING: -50 to 105 deg C THICKNESS: 25 mm MATERIAL: Rubber NBR		20,00	
32	48847601	Khớp giãn nở chịu nhiệt 600 độ C. Installation width: 385mm. Manufacturing width: 585mm. Length: 1600mm. End joining length: 400mm. (Combine-X Expansion joints)	Combine-X Expansion joints	BO	EXPANSION JOINTS SIZE: W 585 * L 1600 mm PRESSURE RATING: -0.14 to 0.07 bar TEMPERATURE RATING: -35 to 600 deg C APPLICATION TYPE: HRSG Exhous ADDITIONAL INFORMATION: Installation width: 385mm; End joining length: 400mm	Combine-X Expansion joints	1,00	
33	51793003	Chemical Pump	Chemical Pump	CAI	PUMP; INJECTION TYPE: CM-10Y-AVF-A15-Z041 MATERIAL: Diaphrag PTFE FLOW RATE: 0.08 L/p APPLICATION: Injection pump Nacl ADDITIONAL INFORMATION: Max press: 1 MPaG; Set include: Pump and Motor	CM-10Y-AVF-A15- Z041	2,00	
34	48645098	Tấm nhựa dày 2mm, vật liệu nhựa tấm teflon	PTFE Sheet	TAM	PLASSTIC; OTHERTYPE: Flat SheetMATERIAL: PTFESIZE: W 1000 * L 1000 * T 2 mmTEMPERATURE RANGE: - 10 to 100 deg CWIDTH: 1000 mmLENGTH: 1000 mmPRESSURE RATING: 12 barADDITIONAL INFORMATION: Cross Tensile strenght: 10 to 30 Mpa	Flat Sheet	2,00	

35	51338004	Cast Iron Gate Valve; WGO-10; DN 400 mm	Cast Iron Gate Valve	CAI	VALVE; DRAIN TYPE: WGO-10 SIZE: DN 400 mm TEMPERATURE RATING: 5-120 deg C PRESSURE RATING: 10 bar MATERIAL: GC200 ADDITIONAL INFORMATION: MANUFACTURER: Wonil valve	WGO-10	1,00	
36	45216070	Bulong inox 304 M16x70 (gồm: Bulông + Đai ốc + Lông đên) (1 cái/bộ)	Bolt and Nut	BO	BOLTS, NUTS, SCREWS; STAINLESS STEEL TYPE: Hex Head SIZE: M16 * 70 BOLT LENGTH: 70 mm MATERIAL CLASS: SS304 INDUSTRY STANDARD: Din 931/933 ADDITIONAL INFORMATION: Include: Bolt, Nut, Washer	M16 * 70	32,00	
37	51202305	KEO CẮY THÉP RAMSET EPCON G5 (Bao gồm 1 súng bắn keo)	G5 Epoxy Adhesive	BO	GLUE; LOCTIE TYPE: Ramset Epcon G5 ADDITIONAL INFORMATION: Include: Dispensing Tool For Epcon G5 (Dispenser Gun)	Ramset Epcon G5	4,00	
38	59001020	Anchor Bolt SS 316L; Fastener; M18 * 180 mm	Anchor Bolt SS 316L	BO	ACCESSORY; SIGN TYPE: Fastener SIZE: M18 * 180 mm APPLICATION: Mechanical rake & car/ Traversing rail Assembly ADDITIONAL INFORMATION: Set include: Anchor bolt, Nut, 2 Washers	M18 * 180	80,00	
39	51202303	Kẹp ray P18, Đường ray xe cào rác trạm bơm tuần hoàn P18 (90 x 80 x 40)	Rail Clips	BO	OTHERSTYPE: P15 MATERIAL: SS400 ADDITIONAL INFORMATION: Traversing Rail Assembly; Mechanical Rake & Car	P18	80,00	

40	51202301	Ray thép P18 - 90x80x40x L5395mm, Đường ray xe cào rác trạm bơm tuần hoàn P18 (90 x 80 x 40)	Rail Steel	CAY	ACCESSORY; SIGN TYPE: P15 SIZE: L 5395 mm FEATURES: Material: Rail Steel E 1103 APPLICATION: Traversing Rail Assembly, Mechanical Rake & Car ADDITIONAL INFORMATION: Bottom W 79.37 * H 79.37 * Head W 42.86 * T 8.33 mm	P15	2,00	
41	51202302	Ray thép P18 - 90x80x40x L5275mm, Đường ray xe cào rác trạm bơm tuần hoàn P18 (90 x 80 x 40)	Rail Steel	CAY	ACCESSORY; SIGN TYPE: P15 SIZE: L 5275 mm FEATURES: Material: Rail Steel E 1103 APPLICATION: Traversing Rail Assembly, Mechanical Rake & Car ADDITIONAL INFORMATION: Bottom W 79.37 * H 79.37 * Head W 42.86 * T 8.33	P15	2,00	
42	34423005	Điện cực nồng độ Clo dư (Analog chlorine dioxide sensor), Order code: CCS51D-1014/0, CCS51D-AA11AD, Serial No: S300B405C00, temp: 0...55 do C, NSX Endress + Hauser.	Digital free chlorine sensor Memosens CCS51D	BO	SENSOR MODEL: CCS51D TYPE: Sensor EQUIPMENT/PACKAGE: 1 item/pk FEATURES: Digital free chlorine sensor MATERIAL: Sensor shaft: POM; Membrane: PVDF; Membrane cap: PVDF; Sealing ring: FKM MOUNTING: Inductive, digital connection head with Memosens PRESSURE RATING: Max. 1 bar (max. 14.5 psi) SIZE: Diameter: 25 mm (0.98 inch); Length: 161 mm (6.34 inch) SUPPLIER: Trace: 0 to 5 mg/l HOCl; Standard: 0 to 20 mg/l HOCl; High: 0 to 200 mg/l HOC TEMPERATURE RANGE: 0 to 55 °C MANUFACTURER: Endress + Hauser APPLICATION: From trace measurement up to free chlorine concentrations of 200 mg/l. ADDITIONAL INFORMATION: Order code: CCS51D-1014/0, CCS51D-AA11AD, Serial No: S300B405C00	CCS51D	1,00	

43	49021015	Ống mềm khí nén gió điều khiển. Type: PFAN-8x1.25-NT. Part No.: 197063	Plastic tubing	M	PLASSTIC; OTHERTYPE: PFAN-8X1,25- NTMATERIAL: PFASIZE: Φ8 mmTEMPERATURE RANGE: - 20 to 150 deg CLENGTH: 1000 - 50000 mmCOLOR: NeutralPRESSURE RATING: - 0.95 to 15 barADDITIONAL INFORMATION: OD: 8 mm; ID:5.9 mm; Part number: 197063; MANUFACTURER: TRAFAG AG			120,00	
44	56065590	ETHERNET SWITCH/FO CONVERTER SPIDER 4TX/1FX. KWZ 604567P0236 PN: SPIDER-SL- 20-04T1M29999SY9HHHH	Ethernet Switch/FO Converter SPIDER 4TX/1FX; SPIDER-SL- 20- 04T1M29999SY9HHHH	PC	COMMUNICATIONS HARDWARE; MODEMS TYPE: SPIDER-SL-20- 04T1M29999SY9HHHH ACCESSORIES: Rail Power Supply RPS 30/80 EEC/120 EEC (CC); Wall mounting plate for DIN rail mounting 40mm - order nr. 942 177-001,wall mounting plate for DIN rail mounting 70mm - order nr. 942 177-002 POWER SUPPLY: 12/24 VDC (9.6 - 32 VDC); Max 100 mA; Max 2.4 W SIZE: D 79 * H 102 * W 26 mm SPEED: 10/100 Mbit/s Ethernet MANUFACTUER: Hirschmann ADDITIONAL INFORMATION: Operating temperature 0 °C to 60 °C	SPIDER-SL-20- 04T1M29999SY9HHHH		1,00	
45	88510437	Máy tính trạm Dell Precision 5820 Tower, Intel Xeon Processor W-2223 3,6GHz 8,25 MB /Ram 16GB /SSD 256 GB/ DVDRW, Nvidia T1000 8GB, Key mouse Dell, Windows 11 Pro.	Dell Precision 5820 Tower		COMPUTER; SERVER MODEL: Intel C422 Chipset / Intel X299 Chipset CONFIGURATION: Intel Xeon, W-2223 Processor, 8.25M Cache, 3.60 GHz up to 3.90 GHz CAPACITY,STORAGE: 2.5inch 256GB SATA Class 20 SSD DEPTH: 518.2 mm HEIGHT: 417.9 mm INTERFACE TYPE: Intel® i219 Gigabit Ethernet controller, 2 USB 2.0; 8 USB 3.1 Type A; 2 USB 3.1 Type C; 1 RJ45; 1 Serial Port; 2 PS2; 1 Audio Line out; 1 Audio Line in/Microphone WEIGHT: 15.9 kg WIDTH: 176.5 mm MANUFACTUER: Dell	Intel C422 Chipset / Intel X299 Chipset		1,00	

					ADDITIONAL INFORMATION: Optical Driver: 8X DVD+/-RW, Graphic: Nvidia T1000 8GB, Key mouse Dell, Windows 11 Pro			
46	48275110	SS-10M0-1-4 Male Connector 10mm Tube ODx1/4".Stainless Steel Swagelok Tube Fitting; SPEC_SHEET:Male Connector, Male NPT Connection 1 Size: 10 mm. Connection 1 Type: Swagelok® Tube Fitting Body Type: Male Connector. Bulkhead: No Bulkhead. Connection 2 Size: 1/4 in. Connection 2 Type: Male NPT.	Male connector	CAI	UNION; PIPE FITTING 1 HEADTYPE: SS-10M0-1-4SIZE: Male NPT 1/4 inMATERIAL: SS316CONNECTION: Swagelok tube fittingDIAMETER: Tube OD 10 mmADDITIONAL INFORMATION: MANUFACTURER: Swagelok	SS-10M0-1-4	32,00	
47	48275112	Đầu nối đực Inox 10mm x1/2" (SS-10M0-1-8)	Tube Fitting, Male Connector; SS-10M-1-8	CAI	UNION; PIPE FITTING 1 HEAD TYPE: SS-10M-1-8 SIZE: 10 mm Tube OD x 1/2 in. Male NPT MATERIAL: SS316 CONNECTION: Swagelok tube fitting DIAMETER: Tube OD 10 mm	SS-10M0-1-8	8,00	
48	56426001	Seamless Tubing SS-T10M-S-1.0M-6ME - 316/316L Seamless Tubing, 10 mm OD x 1.0 mm Wall x 6 Meters; Tube OD: 10 mm; Tube Wall Thickness: 1.0 mm; Material: 316 Stainless steel (6m/cây)	Seamless Tubing, SS-T10M-S-1.0M-6ME	CAY	PIPE; STAINLESS STEEL OUTSIDE DIAMETER: 10 mm NOMINAL WALL THICKNESS: 1 mm MATERIAL STANDARD: SS316/316L ADDITIONAL INFORMATION: Manufacture: SWAGELOK		5,00	
49	88510003	Máy tính để bàn Dell Vostro 3020: Intel Core i3-13100, 8GB DDR4, 512GB SSD, Màn hình: Dell 21 inch, Windows 11 Home 64bit + Office Home	Desktop computer Dell Vostro; Intel® B660 Chipset	BO	COMPUTER; DESKTOP MODEL: Dell Vostro 3020 TYPE: Intel® B660 Chipset CONFIGURATION: CPU Intel® Core i3 - 13100 3.40 GHz turbo 4.50 Ghz, 12M SmartCache, 4 core CAPACITY,STORAGE: SSD 512GB M.2 PCIE NVME SPECIAL FEATURES: RAM memory: 8 GB (1x8GB), 3200MHz, DDR4 (Up to 64GB 3200MHz non-ECC DDR4 memory; 2 U-DIMM slots), Intel UHD 630 Graphics MANUFACTUER: Dell ADDITIONAL INFORMATION: Dell 21 inch screen, Microsoft® Windows®		2,00	

					11 Home 64bit integrated license, Office Home license			
50	36688000	Chuông điện báo cháy. Model: FBB-1501. Type: HOCHIKI MOTOR BELL: DC24V 8mA	Fire alarm bell	CAI	ALARM; ACOUSTICMODEL: FBB-1501TYPE: HOCHIKI MOTOR BELLOUTPUT: ≥ 90dB.POWER SUPPLY: 24 VDC; 8mAADDITIONAL INFORMATION: MANUFACTURER: HOCHIKI/JAPAN	FBB-1501	1,00	

