

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - LÒ HƠI

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
1	48911266	Packing Gland flange of SH electromatic relief valve; 78x25x15 mm; BB-1-119/Item 9	CAI	GLAND PACKING SIZE: 78x25x15 mm TYPE: BB-1-119/Item 9 THICKNESS: 15 mm PRESSURE RATING: 17.95 MPa OUTSIDE DIAMETER: 78 mm MATERIAL: SA105 CARBON STEEL INSIDE DIAMETER: 25 mm APPLICATION: SH ELECTROPNEUMATIC SAFETY VALVE PACKAGING UNIT: 5052299448 ADDITIONAL INFORMATION: PN: 4929401, Manufacturer: Consolidated/china	1
2	58574248	Gasket; NON-METALLIC; OD 106xID 96xT 2.5 mm	CAI	GASKET; NON-METALLIC TYPE: NON-METALLIC SIZE: OD 106xID 96xT 2.5 mm WIDTH: 5 mm LENGTH: 2.5 mm NOMINAL SIZE: 106 mm TEMPERATURE RATING: 525 deg C THICKNESS: 2.5 mm PRESSURE RATING: 20 MPa OUTSIDE DIAMETER: 106 mm MATERIAL: GRAFOIL Flexible Graphite INSIDE DIAMETER: 96 mm APPLICATION: SAFETY VALVES ADDITIONAL INFORMATION: Item 5: PN 4396003,Gasket-GASKET 3-13/16 X 4-7/32 X 1/16 3547	1
3	51992219	Ball & Seat loader of SH electromatic relief valve; RPX-EB VO4; Item 4: Ball & seat assy (4A, 4B, 4C)	BO	ACCESSARY; SAFETY VALVE MODEL/PART NUMBER: RPX-EB VO4 TYPE: Item 4: Ball & seat assy (4A, 4B, 4C) RATED VOLTAGE: 220 VAC RATED CURRENT: 0.27/0.15 A POWER SUPPLY: AC STANDARD: ANSI CLASS PRESSURE RATING: 20 MPa PRESSURE CLASS: CLASS 1500 MANUFACTURER: Consolidated/china ADDITIONAL INFORMATION: 4A: Seat 4B: Ball 4C: Ball & Seat loader of SH electromatic relief valve	1
4	58574249	Packing ring; Packing ring 3547	BO	RING; PACKING TYPE: Packing ring 3547 WIDTH: 7.5 mm PACKAGING UNIT: 5052346079 THICKNESS: 3.8 mm MATERIAL: grafoil APPLICATION: SH electromatic relief valve	1
5	48911275	Packing gland of SH electromatic relief valve; 38/40x23x25/28 mm; Item 10/H1-21	CAI	GLAND PACKING SIZE: 38/40x23x25/28 mm TYPE: Item 10/H1-21 THICKNESS: 25/28 mm PRESSURE RATING: 17.95 MPa OUTSIDE DIAMETER: 38/40 mm MATERIAL: 420 STAINLESS STEEL(CARBIDE COATER) INSIDE DIAMETER: 23 mm PACKAGING UNIT: 5052300238 ADDITIONAL INFORMATION: PN: 4929501, Manufacturer: Consolidated/china	1

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - Lò hơi

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
6	51932573	Poppet valve vòi thổi bụi IK-AH500	BO	VALVE; OTHER MODEL/PART NUMBER: PI 4134 TYPE: IK-AH500 SIZE: N/A PRESSURE RATING: 2 MPa TEMPERATURE RATING: 300 deg C MANUFACTURER: DIAMOND POWER/CHINA MATERIAL: N/A OPERATOR: N/A END STYLE: N/A ADDITIONAL INFORMATION: N/A	2
7	51991073	Poppet valve; PI Form No: 4127; IK555 (IK 5-24)	BO	VALVE; OTHER MODEL/PART NUMBER: PI Form No: 4127 TYPE: IK555 (IK 5-24) SIZE: N/A PRESSURE RATING: 40 bar TEMPERATURE RATING: 400 deg C MANUFACTURER: DIAMOND POWER/CHINA MATERIAL: CARBON STEEL OPERATOR: SEMI-AUTOMATIC END STYLE: FLANGE ADDITIONAL INFORMATION: DUST BLOWING AIR SUPPLY FOR AIR HEATER	2
8	49023014	LANCE TUBE 4"; circular tube; 102x4 in	CAI	TUBE TYPE: circular tube SIZE: 102x4 in WALL THICKNESS: 4 mm MATERIAL: 00Cr17Ni14Mo2 CONNECTION: FLANGE LENGTH: 16000 mm APPLICATION: sootblower ADDITIONAL INFORMATION: LANCE TUBE 4" B&W6330 - NO NOZZLE/Diamond Power/	1
9	30660002	Bộ giá đỡ đường ống cấp hơi thổi bụi IK 555; Chi tiết 22 bản vẽ VA1-BWBC-HCB-M-M1A-DPS-0042	BO	RACKS; STEEL TYPE: TYPE B SIZE: W 194/151xL 238/299 mm MATERIAL: Q235-B APPLICATION: BOILER ISLAND SOOTBLOWNG ADDITIONAL INFORMATION: Chi tiết 22 bản vẽ VA1-BWBC-HCB-M-M1A-DPS-0042, Diamond Power	4
10	30660003	Bộ giá đỡ đường ống cấp hơi thổi bụi IK 545; Chi tiết 22 bản vẽ VA1-BWBC-HCB-M-M1A-DPS-0043	BO	RACKS; STEEL TYPE: SPRING BLOCK TYPE B, ITEM 22 SIZE: HxW 53,94x27.24 mm mm MATERIAL: STEEL Q235-B FINISH: N/A APPLICATION: USED FOR IK 545 SOOTBLOWER SPECIAL REQUIREMENT: SPRING LENGTH 33,12 mm mm PACKAGING UNIT: 1 ADDITIONAL INFORMATION: Chi tiết 22 bản vẽ VA1-BWBC-HCB-M-M1A-DPS-0043	4
11	53276005	spring block type B; item no: 22; Spring block type B	CAI	RACKS; STEEL TYPE: SPRING BLOCK TYPE B, ITEM 22 SIZE: H298xW200 mm MATERIAL: STEEL Q235-B APPLICATION: USED FOR IK 525 SOOTBLOWER ADDITIONAL INFORMATION: Detail 22 in drawing: VA1-BWBC-HCB-M-M1A-DPS-0041	20

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - LÒ HƠI

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
12	53276016	Variable support (SPRING BLOCK TYPE A); SPRING BLOCK TYPE A, ITEM 16; W 150x H 300 mm	BO	RACKS; STEEL TYPE: SPRING BLOCK TYPE A, ITEM 16 SIZE: W 150x H 300 mm MATERIAL: STEEL Q235-B APPLICATION: USED FOR IK 525 SOOTBLOWER ADDITIONAL INFORMATION: IK 525 dust blower holder set, Detail 16, Drawing: VA1-BWBC-HCB-M-M1A-DPS-0041	5
13	51932549	Poppet valve-External loại IK-525	CAI	VALVE; OTHER MODEL/PART NUMBER: N11266-SC1 TYPE: External IK-525 SIZE: N/A PRESSURE RATING: 40 bar TEMPERATURE RATING: 400 deg C MANUFACTURER: DIAMOND POWER/CHINA MATERIAL: cast iron APPLICATION: SOOTBLOWER IK-525 OPERATOR: SEMI-AUTOMATIC END STYLE: FLANGE BOLTS ADDITIONAL INFORMATION: drawing: VA1-BWBC-00100-M-M1A-DAL-0007	2
14	48216037	HGT vòi thổi bụi GGH (Left); IK-525 carriage assy (Left); 600x450x500 mm	CAI	REDUCER; GEAR TYPE: IK-525 carriage assy (Left) SIZE: 600x450x500 mm APPLICATION: Sootblower For GGH CONNECTION: Flange HORSE POWER: 2 RATIO: 60:1 RPM: 54000 rpm SHAFT SIZE: 60 mm TORQUE: 550 Nm MATERIAL: Steel KEY WAY: 16x5 ADDITIONAL INFORMATION: Diamond Power/china	2
15	48216034	HGT vòi thổi bụi GGH; IK-525 carriage assy (right); 600x450x500 mm	CAI	REDUCER; GEAR TYPE: IK-525 carriage assy (right) SIZE: 600x450x500 mm APPLICATION: Sootblower For GGH CONNECTION: Flange HORSE POWER: 2 RATIO: 60:1 RPM: 54000 SHAFT SIZE: 60 mm TORQUE: 550 Nm MATERIAL: Steel KEY WAY: 16x5 ADDITIONAL INFORMATION: Diamond Power/china	2
16	24658026	Vòi thổi bụi GGH; Land tube 71101002301 cho IK525; 127x7 mm	CAI	PIPE; DRIVE TYPE: Land tube 71101002301 cho IK525 SIZE: 127x7 mm LENGTH: 7000 mm CONNECTION: flange WEIGHT: 42 kg WALL THICKNESS: 4 mm ADDITIONAL INFORMATION: Diamond Power/china	2
17	24647013	Vòi thổi bụi GGH; Feed tube loại IK-525 DM3; 68x5 mm	CAI	PIPE; DUCT TYPE: Feed tube loại IK-525 DM3 SIZE: 68x5 mm LENGTH: 246.5 mm INSULATION THICKNESS: 50 mm APPLICATION: USED FOR IK 525 DM3 GGH ADDITIONAL INFORMATION: Diamond Power/china	2

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - LÒ HƠI

STT	Mã VT	Tên vật tư	ĐVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
18	51720054	Bơm cao áp; HD-10903187/2; KD 708-G Kom.Nr	BO	PUMPS MODEL/PART NUMBER: HD-10903187/2 TYPE: KD 708-G Kom.Nr SIZE: N/A POWER RATING: 50 bar PRESSURE RATING: 140 bar MATERIAL: stainless steel RPM: 1500 rpm APPLICATION: GGH high pressure washing pump POLE: 6 PHASE: 3 pha DIMENSION: N/A MANUFACTURER: ucara/china ADDITIONAL INFORMATION: Bơm cao áp, Type: KD 708-G Kom.Nr (Model number):HD-10903187/2	1
19	51337042	Air Relief Valve; IK-525; 75X51X24 mm	CAI	VALVE; RELIEF TYPE: IK-525 SIZE: 75X51X24 mm TEMPERATURE RATING: 410 deg C FLOW RATE: 5–20 m³/h m3/h LIFT PRESSURE: 8.6 bar END STYLE: Threaded DISC MATERIAL: SS 410 CB BODY MATERIAL: SS 410 CB APPLICATION: GGH dust blower vent valve OPERATING PRESSURE: 0.5–10 bar bar ADDITIONAL INFORMATION: Air relief valve 343503-1038 Diamond Power/china	4
20	51932549	Poppet valve-External loại IK-525	CAI	VALVE; OTHER MODEL/PART NUMBER: N11266-SC1 TYPE: External IK-525 SIZE: N/A PRESSURE RATING: 40 bar TEMPERATURE RATING: 400 deg C MANUFACTURER: DIAMOND POWER/CHINA MATERIAL: cast iron APPLICATION: SOOTBLOWER IK-525 OPERATOR: SEMI-AUTOMATIC END STYLE: FLANGE BOLTS ADDITIONAL INFORMATION: drawing: VA1-BWBC-00100-M-M1A-DAL-0007	2
21	48840004	Flexible hose High pressure water flexible hose; 2SN/EN 853; 3/4 in	CAI	HOSE; RUBBER TYPE: 2SN/EN 853 SIZE: 3/4 in MATERIAL: NBR/Steel Wire Braid/Spiral/Abrasion-resistant COLOR: BLACK PARENT FIGURE/MODEL NUMBER: N/A WALL THICKNESS: 5 mm PRESSURE RATING: 25 MPa LENGTH: 650 mm TEMPERATURE RATING: 150 deg C MANUFACTURER: VIỆT NAM APPLICATION: Flexible hose High pressure water flexible hose GGH ADDITIONAL INFORMATION: The connection head at both ends is pressed with a threaded coupling, the sealing type of the connection heads is flat, outer diameter 36 mm - inner diameter 28 mm	10

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - LÒ HƠI

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
22	48840006	GGH washing water supply hydraulic pipe; 2SN/EN 853; 3/4 in	BO	HOSE; RUBBER TYPE: 2SN/EN 853 SIZE: 3/4 in MATERIAL: NBR/Steel Wire Braid/Spiral/Abrasion-resistant COLOR: BLACK PARENT FIGURE/MODEL NUMBER: N/A WALL THICKNESS: 5 mm PRESSURE RATING: 25 MPa LENGTH: 3460 mm TEMPERATURE RATING: 150 deg C MANUFACTURER: H3T/việt nam APPLICATION: Flexible hose High pressure water flexible hose GGH ADDITIONAL INFORMATION: Diameter: 3/4 IN. The two ends of the pipe are pressed with internal threaded joints, the sealing type of the connection ends is flat, 7/8 inch thread, thread pitch 14 threads/inch	10
23	58560555	LP-Bypass valve gasket set TPS9204) Valve Soft Goods Kit Consists: Gasket (1*000003158985); Gasket (1*000003158902); Packing Set (1*255670111); Scraper (0.15Mtr*000101007497); Packing Spacer (1*320401095); Type of Gasket TPS9204; - Gasket (Packing Ring) 430 x 402 x 31; Gasket (Packing Ring) 425 x 396 x 31 mm	BO	GASKETS TYPE: Type of Gasket TPS9204 SIZE: - Gasket (Packing Ring) 430 x 402 x 31; Gasket (Packing Ring) 425 x 396 x 31 mm MATERIAL: Graphite FILLER: graphite INNER RING: Inner ring Gasket: 402; Inner ring Gasket: 396 mm OUTER RING: Outer ring gasket: 430; Outer ring gasket: 425 mm THICKNESS: 31 mm (hight) mm MANUFACTURING METHOD: casting OUTSIDE DIAMETER: Outer ring gasket: 430; Outer ring gasket: 425 mm INSIDE DIAMETER: Inner ring Gasket: 402; Inner ring Gasket: 396 mm CLASS: N/A MPa ADDITIONAL INFORMATION: Drawing: 202833-1CH Pos: 15, 20, 34, 35, 36	1
24	51987006	Valve seat; Type Seat ring - possion number -reference Drawing 202833-1CH	CHIEC	SEAT; VALVE TYPE: Type Seat ring - possion number -reference Drawing 202833-1CH SIZE: N/A SPECIAL FEATURES: Seat ring-pos.004, material X20CrMoV12-1 PRESSURE RATING: Design pressure: Inlet press:4.73 Mpa, outlet press: 1.5Mpa MPa APPLICATION: NBSE 60- 600 LP bypass valve MATERIAL: X20CrMoV11-1 PARENT FIGURE/MODEL NUMBER: Design Code: EN 12516-2 PRESSURE CLASS: hydrotest pressure 275/76 bar bar VALVE TYPE: Type Seat ring - possion number -reference Drawing 202833-1CH ADDITIONAL INFORMATION: Pos. No 004 - reference Drawing 202833-1CH	1

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - LÒ HƠI

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
25	51931037	Bộ vật tư gasket cho van HP Bypass; (TPS9188) Valve Soft Goods Kit Consists: Packing Ring (1*000003158762), Packing Ring (1*000003158888), Packing Set (1*255670111), Scraper (0.15Mtr*000101007497), Packing Spacer (1*320401095), Balance Seal (1*255590882) Drawing: 202775-1CH; Valve Soft Goods Kit Consists for 202775-1CH; 205x229.8x20 mm	BO	SPARE PART; VALVE MODEL/PART NUMBER: (TPS9188) Valve Soft Goods Kit Consists: Packing Ring (1*000003158762), Packing Ring (1*000003158888), Packing Set (1*255670111), Scraper (0.15Mtr*000101007497), Packing Spacer (1*320401095), Balance Seal (1*255590882) Drawing: 202775-1CH TYPE: Valve Soft Goods Kit Consists for 202775-1CH SIZE: 205x229.8x20 mm MATERIAL: Graphite PRESSURE RATING: Design pressure in/out: 18.28/5.03 MPa MANUFACTURER: MMI CCI STANDARD: Hydrotest pressure:275/76 bar NUMBER OF CONTACTS: Phone:+ 6566537000 (singapore) SUPPLIER: IMI-CCI RATED VOLTAGE: 24 VDC RATED CURRENT: 4-20 mA POWER SUPPLY: 24 VDC APPLICATION: HP bypass system TEMPERATURE RANGE: Desing Temprature in /out: 546/364,4 deg C ADDITIONAL INFORMATION: HP/LP bypass steam system	1
26	58560576	(TPS9190) Valve Soft Goods Kit; (TPS9190) Valve Soft Goods Kit Consists: Gasket (2*255590523), Balance Seal (1*255590010), Packing Spacer (1*320408095), Packing Set (1*255670097) Drawing: 202775-2CH Pos: 10, 13, 14, 15; Valve Soft Goods Kit for Drawing: 202775-2CH: Type: Globe; Connect In: Butt Weld OD 168 x THK 22 mm; Connect Out: Butt Weld OD 168 x THK 22 mm	BO	GASKETS TYPE: (TPS9190) Valve Soft Goods Kit Consists: Gasket (2*255590523), Balance Seal (1*255590010), Packing Spacer (1*320408095), Packing Set (1*255670097) Drawing: 202775-2CH Pos: 10, 13, 14, 15 SIZE: Valve Soft Goods Kit for Drawing: 202775-2CH: Type: Globe; Connect In: Butt Weld OD 168 x THK 22 mm; Connect Out: Butt Weld OD 168 x THK 22 mm MATERIAL: graphite+300ss (10); teflon (13); Graphite (14); Carbon (15) SPECIAL REQUIREMENT: Model 100DLC; Drawing: 202775-2CH; Critical Pressure: 22.1 MPa (A); Critical Temperature: 374.2 deg C; Type: Globe STANDARD: Class 2500 ASME THICKNESS: Thickness For gasket (10) Gasket (2*255590523): 3.2 mm MANUFACTURING METHOD: Casting OUTSIDE DIAMETER: For pipe: Connect Out: Butt Weld OD 168 x THK 22 mm INSIDE DIAMETER: For Pipe: Connect In: Butt Weld ID 168 x THK 22 mm CAPS CODE: Model 100DLC; Drawing: 202775-2CH; Serial B901010-1 CLASS: Class 2500 ASME ADDITIONAL INFORMATION: Consists: Gasket (2*255590523), Balance Seal (1*255590010), Packing Spacer (1*320408095), Packing Set (1*255670097) Drawing: 202775-	1

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - LÒ HƠI

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
27	51934219	Plug Assembly; Model 100DLC/ Part no: 202775-2CH; Type: Globe; Connect In: Butt Weld OD 168 x THK 22 mm; Connect Out: Butt Weld OD 168 x THK 22 mm; Size Rating: 6x6, Globe, 2500ASME in	CHIEC	DISC, PLUG,STEM; VALVE MODEL/PART NUMBER: Model 100DLC/ Part no: 202775-2CH TYPE: Type: Globe; Connect In: Butt Weld OD 168 x THK 22 mm; Connect Out: Butt Weld OD 168 x THK 22 mm SIZE: Size Rating: 6x6, Globe, 2500ASME in MATERIAL: Disc material: 410ss, Body Material: A216-WCB MANUFACTURER: DRAG VALVE LENGTH: For Valve: length 609.6 mm mm PRESSURE RATING: max pressure 42.5 Mpa (at 100 o F) MPa DIMENSION: Pipe: Connect In: Butt Weld OD 168 x THK 22 mm; Connect Out: Butt Weld OD 168 x THK 22 mm PACKAGING UNIT: set APPLICATION: Spray for HPbypass valve SUPPLIER: IMI-CCI CONDUIT SIZE: Connect In: Butt Weld OD 168 x THK 22 mm; Connect Out: Butt Weld OD 168 x THK 22 mm TAPER: 37.5 deg C CONNECTION: Butt Weld ADDITIONAL INFORMATION: Plug Assembly for HP Spray water control valve, S/N: B90101-01, 02 (01 bộ bao gồm plug chi tiết số 6 và Stem chi tiết số 7 trên bản vẽ 202775-2CH đính kèm)	1
28	58560586	(TPS9192) Valve Soft Goods Kit; Consists: Seat Gasket (2*61110933AE), Bonnet Gasket (1*61113713AE), Balance Seal (1*6130651AH), Packing Set (1*6122538AA) Drawing: 202775-3CH Pos: 8, 9, 10, 13; Globe valve 6x6": Inlet connect OD 168x22, outlet Connect OD 168x22	BO	GASKETS TYPE: Consists: Seat Gasket (2*61110933AE), Bonnet Gasket (1*61113713AE), Balance Seal (1*6130651AH), Packing Set (1*6122538AA) Drawing: 202775-3CH Pos: 8, 9, 10, 13 SIZE: Globe valve 6x6": Inlet connect OD 168x22, outlet Connect OD 168x22 MATERIAL: Balance seal (8): 316ss+ teflon; Gasket (9): 304+ Graphite; Gasket (10): 304+ Graphite; Packing set (13): Graphite SPECIAL REQUIREMENT: Standard CCI tagging only FILLER: Filler for gasket: Graphite DIMENSIONAL STANDARD: Standard CCI STANDARD: ASME 2500 (Standard CCI tagging only) THICKNESS: For gasket :3.2 mm MANUFACTURING METHOD: casting OUTSIDE DIAMETER: For piping connection:outlet OD 168x22 mm INSIDE DIAMETER: For piping connection: Inlet OD 168x22 mm CLASS: ASME Class 2500 ADDITIONAL INFORMATION: Consists: Seat Gasket (2*61110933AE), Bonnet Gasket (1*61113713AE), Balance Seal (1*6130651AH), Packing Set (1*6122538AA) Drawing: 202775-3CH Pos: 8, 9, 10, 13	1
29	51794018	Hydraulic oil pump for feed water pump, Drawing: (WBG)B2620C-589000A; W.02.Z.000006; 279.1x219.4 mm mm	BO	PUMP; OIL TYPE: piston pump SIZE: 279.1x219.4 mm mm HORSE POWER: 45 kW RPM: 1450 rpm NUMBER OF STAGES: type piston pump (Non of Stages) MATERIAL: Metal FLOW RATE: Max Flow rate: 76 L/min APPLICATION: EHC oil for BFPT system ADDITIONAL INFORMATION: Piston pump, Item no: W.02.Z.000006 - referenceDrawing: (WBG)B2620C-589000A	1

PHỤ LỤC 1 -VẬT TƯ HỆ THỐNG TUABIN - Lò hơi

STT	Mã VT	Tên vật tư	DVT	Quy cách / Đặc tính kỹ thuật / NSX	Số lượng
30	56319002	Sparepart for Control valve for deaerator water level-Sealing Assembly Spare part for valve 10" special 300# class SD700-160.DA; Model valve: SD10; Valve type:Main CV, DN 10", Class 300SPL, WCB, BW, SD-700-160DA; Control valve Serial No:000002610062& 10076; set	SET	CONTROL VALVE ACTUATOR SPARE PARTS MODEL: Model valve: SD10 TYPE: Valve type:Main CV, DN 10", Class 300SPL, WCB, BW, SD-700-160DA PART NUMBER: Control valve Serial No:000002610062& 10076 EQUIPMENT/PACKAGE: set MATERIAL: Packing material: Grafoil, gasket: SS304+Graphite MANUFACTURER: Copes vucal, spx valve control ADDITIONAL INFORMATION: Dearator water level control	2
31	56319001	Bộ Spear part kit Gasket and Packing Van CV; CV valve Start-up DN 6"	BO	CONTROL VALVE ACTUATOR SPARE PARTS MODEL: Model GS6 TYPE: CV valve Start-up DN 6" PART NUMBER: CV serial N.o: 1000002610063&10077 EQUIPMENT/PACKAGE: Single Packed INSIDE DIAMETER: 6" in WIDTH: 30 (+- 0.06) in MATERIAL: Packing Material: Grapfoil MANUFACTURER: Copes vulcan ADDITIONAL INFORMATION: Class 300SPL, WCB, BW, SD-700-100DA, Customer PO: PO/008/2011 , Serial No: 1000002610063&10077	2